

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020Revision date 30-Apr-2021
Revision Number 1.04**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Product Name** BOSTIK FLEXACRYL GREY
Pure substance/mixture Mixture**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended use** Primers, Sealers, and Undercoaters.
Uses advised against None known.**1.3. Details of the supplier of the safety data sheet****Company Name**Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36**E-mail address** SDS.box-EU@bostik.com**1.4. Emergency telephone number****Emergency Telephone** No information available**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

Flammable liquids Category 3 - (H226)**2.2. Label elements****Signal word**

Warning

Hazard statements

H226 - Flammable liquid and vapour.

EU Specific Hazard StatementsEUH208 - Contains Fatty acids, C14-18 and C16-18-unsatd., maleated. May produce an allergic reaction
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280 - Wear protective gloves and eye/face protection
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Propylene glycol monomethyl ether acetate	203-603-9	108-65-6	20 - 25	Flam. Liq. 3 (H226)		01-2119475791-29-XXXX
Propylene glycol monomethyl ether	203-539-1	107-98-2	5 - <10	STOT SE 3 (H336) Flam. Liq. 3 (H226)		01-2119457435-35-xxxx
1-methoxy-2-propyl acetate	203-603-9	108-65-6	5 - <10	Flam Liq. 3 (H226) STOT SE 3 (H336)		01-2119475791-29-xxxx
Titanium dioxide	236-675-5	13463-67-7	5 - <10	Carc. 2 (H351i)		01-2119489379-17-XXXX
Xylenes (o-, m-, p-isomers)	215-535-7	1330-20-7	0.1- <1	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226) Aquatic Chronic		01-2119488216-32-XXXX

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Ethylbenzene	202-849-4	100-41-4	0.1- <1	3 (H412) STOT RE 2 (H373) Asp. Tox. 1 (H304) Acute Tox. 4 (H332) Flam Liq. 2 (H225) Aquatic Chronic 3 (H412)		01-2119489370-35-XXXX
Fatty acids, C14-18 and C16-18-unsatd., maleated	288-306-2	85711-46-2	0.1- <1	Skin Irrit. 2 (H315) Skin Sens. 1 (H317)		01-2119976378-19-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon dioxide (CO₂). Hydrogen chloride. Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

7.3. Specific end use(s)

Specific use(s)
Primers, Sealers, and Undercoaters.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Propylene glycol monomethyl ether acetate 108-65-6	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ *
Propylene glycol monomethyl ether 107-98-2	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³ *
1-methoxy-2-propyl acetate 108-65-6	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ *
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ *
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 442 mg/m ³ STEL: 200 ppm STEL: 884 mg/m ³ *

Derived No Effect Level (DNEL) No information available

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Derived No Effect Level (DNEL)			
Propylene glycol monomethyl ether acetate (108-65-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	275 mg/m ³	
worker Short term Systemic health effects	Inhalation	550 mg/m ³	
worker Long term Local health effects	Inhalation	550 mg/m ³	
worker Long term Systemic health effects	Dermal	796 mg/kg bw/d	

Propylene glycol monomethyl ether (107-98-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Inhalation	553.5 mg/m ³	
worker Short term Local health effects	Inhalation	553.5 mg/m ³	
worker Long term Systemic health effects	Dermal	183 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	369 mg/m ³	

1-methoxy-2-propyl acetate (108-65-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	275 mg/m ³	
worker Long term Systemic health effects	Dermal	796 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

Xylenes (o-, m-, p- isomers) (1330-20-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	180 mg/kg bw/d	
Long term Systemic health effects worker	Inhalation	77 mg/m ³	

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Short term Local health effects Systemic health effects worker	Inhalation	289 mg/m ³	
---	------------	-----------------------	--

Derived No Effect Level (DNEL)			
Propylene glycol monomethyl ether acetate (108-65-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	33 mg/m ³	
Consumer Long term Local health effects	Inhalation	33 mg/m ³	
Consumer Long term Systemic health effects	Dermal	320 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	36 mg/kg bw/d	

Propylene glycol monomethyl ether (107-98-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	78 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	43.9 mg/m ³	
Consumer Long term Systemic health effects	Oral	33 mg/kg bw/d	

1-methoxy-2-propyl acetate (108-65-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	33 mg/m ³	
Consumer Long term Local health effects	Inhalation	33 mg/m ³	
Consumer Long term Systemic health effects	Dermal	320 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	36 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Propylene glycol monomethyl ether acetate (108-65-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.635 mg/l
Marine water	0.064 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	3.29 mg/kg dry weight
Marine sediment	0.329 mg/kg dry weight
Soil	0.29 mg/kg dry weight

Propylene glycol monomethyl ether (107-98-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Sewage treatment plant	100 mg/l
Freshwater sediment	52.3 mg/kg dry weight
Marine sediment	5.2 mg/kg dry weight
Soil	4.59 mg/kg dry weight

1-methoxy-2-propyl acetate (108-65-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.635 mg/l
Marine water	0.064 mg/l
Sewage treatment plant	100 mg/l
Freshwater sediment	3.29 mg/l
Marine sediment	0.329 mg/kg dry weight
Soil	0.29 mg/kg dry weight

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Tight sealing safety goggles.
Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic or rubber.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Colour Grey
Odour Characteristic
Odour threshold No information available

Property	Values	Remarks • Method
pH	No data available	
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	120 °C	
Flash point	> 32 °C	No information available
Evaporation rate	No data available	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	No data available	
Water solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%) No information available
VOC Content (%)
Liquid Density 1.0

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.
Eye contact Based on available data, the classification criteria are not met.
Skin contact Based on available data, the classification criteria are not met.
Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 410.7524 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propylene glycol monomethyl ether acetate 108-65-6	=8532 mg/kg (Rattus)	> 5 g/kg (Oryctolagus cuniculus)	= 16000 mg/m ³ (Rat) 6 h
Propylene glycol monomethyl ether 107-98-2	>3500 mg/Kg (Rattus)	>2000 mg/Kg (Rattus)	>7559 ppm (Rattus) 6 h
1-methoxy-2-propyl acetate 108-65-6	=8532 mg/kg (Rattus)	> 5 g/kg (Oryctolagus cuniculus)	= 16000 mg/m ³ (Rat) 6 h
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
Xylenes (o-, m-, p- isomers) 1330-20-7	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	=>47635 mg/L (Rattus) 4 h = >5000 ppm (Rattus) 4 h
Ethylbenzene 100-41-4	=3500 mg/kg (Rattus)	= 15400 mg/kg (Oryctolagus cuniculus)	=17.4 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide 13463-67-7	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Propylene glycol monomethyl ether acetate 108-65-6	-	LC50: =161mg/L (96h, Pimephales promelas)	-	EC50: >500mg/L (48h, Daphnia magna)		
Propylene glycol monomethyl ether 107-98-2	-	LC50: 4600 - 10000mg/L (96h, Leuciscus idus) LC50: =20.8g/L (96h, Pimephales)	-	EC50: =23300mg/L (48h, Daphnia magna)		

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

		promelas)				
1-methoxy-2-propyl acetate 108-65-6	-	LC50: =161mg/L (96h, Pimephales promelas)	-	EC50: >500mg/L (48h, Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 2.6 mg/L (Oncorhynchus mykiss) (OECD 203)	EC50 = 0.0084 mg/L 24 h	EC50 48 h = 3.4 mg/L (Dappnia magna)		
Ethylbenzene 100-41-4	EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchner iella subcapitata)	LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)		
Fatty acids, C14-18 and C16-18-unsatd., maleated 85711-46-2	-	LC50: >100mg/L (96h, Danio rerio)	-	-		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
1-methoxy-2-propyl acetate (108-65-6)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	83%	Readily biodegradable
Xylenes (o-, m-, p- isomers) (1330-20-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	biodegradation	87.8 % Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Propylene glycol monomethyl ether acetate 108-65-6	0.43	-
Propylene glycol monomethyl ether 107-98-2	-0.437	2
1-methoxy-2-propyl acetate 108-65-6	0.43	-
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15	15
Ethylbenzene	3.2	15

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

100-41-4		
----------	--	--

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment . The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Propylene glycol monomethyl ether acetate 108-65-6	The substance is not PBT / vPvB
Propylene glycol monomethyl ether 107-98-2	The substance is not PBT / vPvB
1-methoxy-2-propyl acetate 108-65-6	The substance is not PBT / vPvB
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply
Xylenes (o-, m-, p- isomers) 1330-20-7	The substance is not PBT / vPvB
Ethylbenzene 100-41-4	The substance is not PBT / vPvB
Fatty acids, C14-18 and C16-18-unsatd., maleated 85711-46-2	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number	UN1263
14.2 Proper Shipping Name	Paint related material
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	III
Description	UN1263, Paint related material, 3, III, (D/E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	163, 650, 367

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Classification code F1
Tunnel restriction code (D/E)
Limited Quantity (LQ) 5 L
ADR Hazard Id (Kemmler Number) 30

IMDG

14.1 UN number or ID number UN1263
14.2 Proper Shipping Name Paint related material
14.3 Transport hazard class(es) 3
14.4 Packing group III
Description UN1263, Paint related material, 3, III, (32°C c.c.)
14.5 Marine pollutant NP
14.6 Special Provisions 163, 223, 367, 955
Limited Quantity (LQ) 5 L
EmS-No F-E, S-E
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1263
14.2 Proper Shipping Name Paint related material
14.3 Transport hazard class(es) 3
14.4 Packing group III
Description UN1263, Paint related material, 3, III
14.5 Environmental hazards Not applicable
14.6 Special Provisions A3, A72, A192
Limited Quantity (LQ) 10 L
ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supercedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS
P5b - FLAMMABLE LIQUIDS
P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Propylene glycol monomethyl ether acetate 108-65-6	RG 84
Propylene glycol monomethyl ether 107-98-2	RG 84
1-methoxy-2-propyl acetate 108-65-6	RG 84
Xylenes (o-, m-, p- isomers) 1330-20-7	RG 4bis, RG 84 RG 5, RG 14, RG 15, RG 15bis, RG 20bis RG 84
Ethylbenzene 100-41-4	RG 84

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

Flammable liquid (R10), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 3

Water hazard class (WGK) slightly hazardous to water (WGK 1)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens
Xylenes (o-, m-, p- isomers) 1330-20-7	Development (Category 2)

Denmark

Registration number(s) (P-no.) No information available

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

SAFETY DATA SHEET

BOSTIK FLEXACRYL GREY
Supersedes Date: 09-Oct-2020

Revision date 30-Apr-2021
Revision Number 1.04

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour
H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 30-Apr-2021

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet